
cdrouter.py Documentation

Release 0.0.18

QA Cafe

January 17, 2017

1	Introduction	1
1.1	Download & Install	1
1.2	Usage	1
2	Reference	3
2.1	cdrouter	3
2.2	cdrouter.CDRouter	3
2.3	cdrouter.configs.ConfigsService	4
2.4	cdrouter.devices.DevicesService	5
2.5	cdrouter.jobs.JobsService	6
2.6	cdrouter.packages.PackagesService	6
2.7	cdrouter.results.ResultsService	7
2.8	cdrouter.testresults.TestResultsService	8
2.9	cdrouter.annotations.AnnotationsService	9
2.10	cdrouter.captures.CapturesService	9
2.11	cdrouter.highlights.HighlightsService	9
2.12	cdrouter.imports.ImportsService	10
2.13	cdrouter.exports.ExportsService	10
2.14	cdrouter.history.HistoryService	10
2.15	cdrouter.system.SystemService	10
2.16	cdrouter.tags.TagsService	11
2.17	cdrouter.testsuites.TestsuitesService	12
2.18	cdrouter.users.UsersService	12
	Python Module Index	15

Introduction

cdrouter is a simple Python wrapper for the CDRouter Web API. <https://support.qacafe.com/cdrouter-web-api/>
For more information on CDRouter, please visit <http://www.qacafe.com/>.

1.1 Download & Install

cdrouter is available on PyPI.

```
$ pip install -U cdrouter
```

1.2 Usage

```
import time
from cdrouter import CDRouter
from cdrouter.jobs import Job

c = CDRouter('http://localhost:8015', token='deadbeef')

for p in c.packages.list(filter=['tags@>{noretry}'], limit='none'):
    print('Launching package ' + p.name)

    j = c.jobs.launch(Job(package_id=p.id, extra_cli_args='-testvar myvar=example'))

    while j.result_id == None:
        time.sleep(1)
        j = c.jobs.get(j.id)

    print('    Result-ID: ' + j.result_id)

print('done.')
```


2.1 cdrouter

Python client for the CDRouter Web API.

2.2 cdrouter.CDRouter

class `cdrouter.CDRouter` (*base, token=None, insecure=False*)
Service for accessing the CDRouter Web API.

bulk_copy (*base, resource, ids, schema*)
Send an authorized POST request to bulk copy a set of resources.

bulk_delete (*base, resource, ids=None, filter=None, all=False*)
Send an authorized POST request to bulk delete a set of resources.

bulk_edit (*base, resource, fields, ids=None, filter=None, all=False, testvars=None*)
Send an authorized POST request to bulk edit a set of resources.

bulk_export (*base, ids, params=None*)
Send an authorized GET request to bulk export a set of resources.

create (*base, resource*)
Send an authorized POST request to create a new resource.

delete (*path, params=None*)
Send an authorized DELETE request.

delete_id (*base, id*)
Send an authorized DELETE request to delete a resource by ID.

edit (*base, id, resource*)
Send an authorized PATCH request to edit a resource.

edit_shares (*base, id, user_ids*)
Send an authorized PATCH request to edit a resource's shares.

export (*base, id, format='gz', params=None*)
Send an authorized GET request to export a resource.

get (*path, params=None, stream=None*)
Send an authorized GET request.

get_id (*base, id, params=None*)
Send an authorized GET request to get a resource by ID.

get_shares (*base, id*)
Send an authorized GET request to get a resource's shares.

list (*base, filter=None, type=None, sort=None, limit=None, page=None, format=None*)
Send an authorized GET request for a collection.

patch (*path, json, params=None*)
Send an authorized PATCH request.

post (*path, json=None, data=None, params=None, files=None*)
Send an authorized POST request.

2.3 cdrouter.configs.ConfigsService

class `cdrouter.configs.ConfigsService` (*service*)
Service for accessing CDRouter Configs.

bulk_copy (*ids*)
Bulk copy a set of configs.

bulk_delete (*ids=None, filter=None, all=False*)
Bulk delete a set of configs.

bulk_edit (*_fields, ids=None, filter=None, all=False, testvars=None*)
Bulk edit a set of configs.

bulk_edit_testvars (*id, testvars*)
Bulk edit a config's testvars.

bulk_export (*ids*)
Bulk export a set of configs.

check_config (*contents*)
Process config contents with `cdrouter-cli -check-config`.

create (*resource*)
Create a new config.

delete (*id*)
Delete a config.

delete_testvar (*id, name, group=None*)
Delete a testvar in a config. Deleting a testvar unsets any explicitly configured value for it in the config.

edit (*resource*)
Edit a config.

edit_shares (*id, user_ids*)
Edit shares for a config.

edit_testvar (*id, resource*)
Edit a testvar in a config.

export (*id*)
Export a config.

get (*id, format=None*)
Get a config.

get_networks (*contents*)
Process config contents with `cdrouter-cli -print-networks-json`.

get_new ()
Get output of `cdrouter-cli -new-config`.

get_plaintext (*id*)
Get a config as plaintext.

get_shares (*id*)
Get shares for a config.

get_testvar (*id, name, group=None*)
Get a testvar from a config.

list (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of configs.

list_testvars (*id*)
Get a list of a config's testvars.

upgrade_config (*contents*)
Process config contents with `cdrouter-cli -upgrade-config`.

2.4 cdrouter.devices.DevicesService

class `cdrouter.devices.DevicesService` (*service*)
Service for accessing CDRouter Devices.

bulk_copy (*ids*)
Bulk copy a set of devices.

bulk_delete (*ids=None, filter=None, all=False*)
Bulk delete a set of devices.

bulk_edit (*_fields, ids=None, filter=None, all=False*)
Bulk edit a set of devices.

bulk_export (*ids*)
Bulk export a set of devices.

create (*resource*)
Create a new device.

delete (*id*)
Delete a device.

edit (*resource*)
Edit a device.

edit_shares (*id, user_ids*)
Edit shares for a device.

export (*id*)
Export a device.

get (*id*)
Get a device.

get_shares (*id*)
Get shares for a device.

list (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of devices.

2.5 cdrouter.jobs.JobsService

class `cdrouter.jobs.JobsService` (*service*)
Service for accessing CDRouter Jobs.

bulk_delete (*ids=None, filter=None, all=False*)
Bulk delete a set of jobs.

bulk_launch (*jobs=None, filter=None, all=False*)
Bulk launch a set of jobs.

delete (*id*)
Delete a job.

edit (*resource*)
Edit a tag.

get (*id*)
Get a job.

launch (*resource*)
Launch a new job.

list (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of jobs.

2.6 cdrouter.packages.PackagesService

class `cdrouter.packages.PackagesService` (*service*)
Service for accessing CDRouter Packages.

analyze (*id*)
Get a list of tests that will be skipped for a package.

bulk_copy (*ids*)
Bulk copy a set of packages.

bulk_delete (*ids=None, filter=None, all=False*)
Bulk delete a set of packages.

bulk_edit (*_fields, ids=None, filter=None, all=False*)
Bulk edit a set of packages.

bulk_export (*ids*)
Bulk export a set of packages.

create (*resource*)
Create a new package.

delete (*id*)
Delete a package.

edit (*resource*)
Edit a package.

edit_shares (*id*, *user_ids*)
 Edit shares for a package.

export (*id*)
 Export a package.

get (*id*)
 Get a package.

get_shares (*id*)
 Get shares for a package.

list (*filter=None*, *type=None*, *sort=None*, *limit=None*, *page=None*)
 Get a list of packages.

2.7 cdrouter.results.ResultsService

class `cdrouter.results.ResultsService` (*service*)
 Service for accessing CDRouter Results.

all_stats ()
 Compute stats for all results.

bulk_copy (*ids*)
 Bulk copy a set of results.

bulk_delete (*ids=None*, *filter=None*, *all=False*)
 Bulk delete a set of results.

bulk_edit (*_fields*, *ids=None*, *filter=None*, *all=False*)
 Bulk edit a set of results.

bulk_export (*ids*, *exclude_captures=False*)
 Bulk export a set of results.

delete (*id*)
 Delete a result.

download_logdir_archive (*id*, *filename*, *format='zip'*, *exclude_captures=False*)
 Download logdir archive in tgz or zip format.

edit (*resource*)
 Edit a result.

edit_shares (*id*, *user_ids*)
 Edit shares for a result.

export (*id*, *exclude_captures=False*)
 Export a result.

get (*id*)
 Get a result.

get_logdir_file (*id*, *filename*)
 Download a logdir file.

get_shares (*id*)
 Get shares for a result.

get_test_metric (*id*, *name*, *metric*, *format=None*)
 Get a test metric.

get_test_metric_csv (*id, name, metric*)
Get a test metric as CSV.

list (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of results.

list_csv (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of results as CSV.

list_logdir (*id, filter=None, sort=None*)
Get a list of logdir files.

pause (*id, when=None*)
Pause a running result.

pause_end_of_loop (*id*)
Pause a running result at the end of the current loop.

pause_end_of_test (*id*)
Pause a running result at the end of the current test.

set_stats (*ids*)
Compute stats for a set of results.

single_stats (*id*)
Compute stats for a result.

stop (*id, when=None*)
Stop a running result.

stop_end_of_loop (*id*)
Stop a running result at the end of the current loop.

stop_end_of_test (*id*)
Stop a running result at the end of the current test.

unpause (*id*)
Unpause a running result.

2.8 cdrouter.testresults.TestResultsService

class `cdrouter.testresults.TestResultsService` (*service*)
Service for accessing CDRouter TestResults.

edit (*id, resource*)
Edit a test result.

get (*id, seq*)
Get a test result.

get_log (*id, seq, offset=None, limit=None, filter=None, packets=None, timestamp_format=None*)
Get a test result's log.

get_log_plaintext (*id, seq*)
Get a test result's log as plaintext.

list (*id, filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of test results.

list_csv (*id, filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of test results as CSV.

2.9 cdrouter.annotations.AnnotationsService

class `cdrouter.annotations.AnnotationsService` (*service*)

Service for accessing CDRouter Annotations.

create_or_edit (*id, seq, resource*)

Create or edit an annotation.

delete (*id, seq, line*)

Delete an annotation.

get (*id, seq, line*)

Get an annotation.

list (*id, seq*)

Get a list of annotations.

2.10 cdrouter.captures.CapturesService

class `cdrouter.captures.CapturesService` (*service*)

Service for accessing CDRouter Captures.

ascii (*id, seq, intf, filter=None, frame=None, inline=False*)

Get a capture's ASCII (hex dump).

decode (*id, seq, intf, filter=None, frame=None, inline=False*)

Get a capture's decode.

download (*id, seq, intf, inline=False*)

Download a capture as a PCAP file.

get (*id, seq, intf*)

Get a capture.

list (*id, seq*)

Get a list of captures.

send_to_cloudshark (*id, seq, intf, inline=False*)

Send a capture to a CloudShark Appliance. Both `cloudshark_appliance_url` and `cloudshark_appliance_token` must be properly configured via system preferences.

summary (*id, seq, intf, filter=None, inline=False*)

Get a capture's summary.

2.11 cdrouter.highlights.HighlightsService

class `cdrouter.highlights.HighlightsService` (*service*)

Service for accessing CDRouter Highlights.

create_or_edit (*id, seq, resource*)

Create or edit a highlight.

delete (*id, seq, line*)

Get a highlight.

get (*id, seq, line*)

Get a highlight.

list (*id, seq*)
Get a list of highlights.

2.12 cdrouter.imports.ImportsService

class `cdrouter.imports.ImportsService` (*service*)
Service for accessing CDRouter Imports.

commit (*id, imprec*)
Commit a staged import.

delete (*id*)
Delete a staged import.

get (*id*)
Get a staged import.

get_commit_request (*id*)
Get a commit request for a staged import.

list ()
Get a list of staged (in-progress) imports.

stage_import_from_file (*fd, filename='upload.gz'*)
Stage an import from a file upload.

stage_import_from_filesystem (*filepath*)
Stage an import from a filesystem path.

stage_import_from_url (*url, token=None, insecure=False*)
Stage an import from a URL to another CDRouter system.

2.13 cdrouter.exports.ExportsService

class `cdrouter.exports.ExportsService` (*service*)
Service for accessing CDRouter Exports.

bulk_export (*config_ids=None, device_ids=None, package_ids=None, result_ids=None, exclude_captures=False*)
Bulk export a set of configs, devices, packages and results.

2.14 cdrouter.history.HistoryService

class `cdrouter.history.HistoryService` (*service*)
Service for accessing CDRouter History.

list (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of history entries.

2.15 cdrouter.system.SystemService

class `cdrouter.system.SystemService` (*service*)
Service for accessing CDRouter System.

check_for_lounge_upgrade (*email, password*)
Check the CDRouter Support Lounge for eligible upgrades using your Support Lounge email & password.

diagnostics ()
Get system diagnostics from cdrouter-diag output.

edit_preferences (*resource*)
Edit preferences in /usr/cdrouter-data/etc/config.yml.

get_preferences ()
Get preferences from /usr/cdrouter-data/etc/config.yml.

hostname ()
Get system hostname.

info ()
Get system info from cdrouter-cli -info output.

interfaces (*addresses=False*)
Get system interfaces.

latest_lounge_release ()
Get the latest release of CDRouter from the CDRouter Support Lounge.

live ()
Get CDRouter Live info from cdrouter-cli -live output.

lounge_update_license ()
Download & install a license for your CDRouter system from the CDRouter Support Lounge.

lounge_upgrade (*email, password, release_id*)
Download & install an upgrade from the CDRouter Support Lounge using your Support Lounge email & password. Please note that any running tests will be stopped.

manual_update_license (*fd, filename='cdrouter.lic'*)
“Update the license on your CDRouter system manually by uploading a .lic license from the CDRouter Support Lounge.

manual_upgrade (*fd, filename='cdrouter.bin'*)
Upgrade CDRouter manually by uploading a .bin installer from the CDRouter Support Lounge. Please note that any running tests will be stopped.

restart ()
Restart CDRouter web interface. Please note that any running tests will be stopped.

time ()
Get system time.

2.16 cdrouter.tags.TagsService

class `cdrouter.tags.TagsService` (*service*)
Service for accessing CDRouter Tags.

delete (*name*)
Delete a tag.

edit (*resource*)
Edit a tag.

get (*name*)
Get a tag.

list (*resource=None, sort=None*)
Get a list of tags.

2.17 cdrouter.testsuites.TestsuitesService

class `cdrouter.testsuites.TestsuitesService` (*service*)
Service for accessing CDRouter Testsuites.

get_error (*name*)
Get a error.

get_group (*name*)
Get a group.

get_label (*name*)
Get a label.

get_module (*name*)
Get a module.

get_test (*name*)
Get a test.

get_testvar (*name*)
Get a testvar.

info ()
Get testsuite info.

list_errors (*filter=None, type=None, sort=None*)
Get a list of errors.

list_groups (*filter=None, type=None, sort=None*)
Get a list of groups.

list_labels (*filter=None, type=None, sort=None*)
Get a list of labels.

list_modules (*filter=None, type=None, sort=None*)
Get a list of modules.

list_tests (*filter=None, type=None, sort=None*)
Get a list of tests.

list_testvars (*filter=None, type=None, sort=None*)
Get a list of testvars.

search (*query*)
Perform full text search of testsuite.

2.18 cdrouter.users.UsersService

class `cdrouter.users.UsersService` (*service*)
Service for accessing CDRouter Users.

bulk_copy (*ids*)
Bulk copy a set of users.

bulk_delete (*ids=None, filter=None, all=False*)
Bulk delete a set of users.

bulk_edit (*_fields, ids=None, filter=None, all=False*)
Bulk edit a set of users.

change_password (*id, new, old=None, change_token=True*)
Change a user's password.

change_token (*id*)
Change a user's token.

create (*resource*)
Create a new user.

delete (*id*)
Delete a user.

edit (*resource*)
Edit a user.

get (*id*)
Get a user.

list (*filter=None, type=None, sort=None, limit=None, page=None*)
Get a list of users.

C

cdrouter, 3

A

all_stats() (cdrouter.results.ResultsService method), 7
 analyze() (cdrouter.packages.PackagesService method), 6
 AnnotationsService (class in cdrouter.annotations), 9
 ascii() (cdrouter.captures.CapturesService method), 9

B

bulk_copy() (cdrouter.CDRouter method), 3
 bulk_copy() (cdrouter.configs.ConfigsService method), 4
 bulk_copy() (cdrouter.devices.DevicesService method), 5
 bulk_copy() (cdrouter.packages.PackagesService method), 6
 bulk_copy() (cdrouter.results.ResultsService method), 7
 bulk_copy() (cdrouter.users.UsersService method), 12
 bulk_delete() (cdrouter.CDRouter method), 3
 bulk_delete() (cdrouter.configs.ConfigsService method), 4
 bulk_delete() (cdrouter.devices.DevicesService method), 5
 bulk_delete() (cdrouter.jobs.JobsService method), 6
 bulk_delete() (cdrouter.packages.PackagesService method), 6
 bulk_delete() (cdrouter.results.ResultsService method), 7
 bulk_delete() (cdrouter.users.UsersService method), 12
 bulk_edit() (cdrouter.CDRouter method), 3
 bulk_edit() (cdrouter.configs.ConfigsService method), 4
 bulk_edit() (cdrouter.devices.DevicesService method), 5
 bulk_edit() (cdrouter.packages.PackagesService method), 6
 bulk_edit() (cdrouter.results.ResultsService method), 7
 bulk_edit() (cdrouter.users.UsersService method), 13
 bulk_edit_testvars() (cdrouter.configs.ConfigsService method), 4
 bulk_export() (cdrouter.CDRouter method), 3
 bulk_export() (cdrouter.configs.ConfigsService method), 4
 bulk_export() (cdrouter.devices.DevicesService method), 5
 bulk_export() (cdrouter.exports.ExportsService method), 10

bulk_export() (cdrouter.packages.PackagesService method), 6
 bulk_export() (cdrouter.results.ResultsService method), 7
 bulk_launch() (cdrouter.jobs.JobsService method), 6

C

CapturesService (class in cdrouter.captures), 9
 CDRouter (class in cdrouter), 3
 cdrouter (module), 3
 change_password() (cdrouter.users.UsersService method), 13
 change_token() (cdrouter.users.UsersService method), 13
 check_config() (cdrouter.configs.ConfigsService method), 4
 check_for_lounge_upgrade() (cdrouter.system.SystemService method), 10
 commit() (cdrouter.imports.ImportsService method), 10
 ConfigsService (class in cdrouter.configs), 4
 create() (cdrouter.CDRouter method), 3
 create() (cdrouter.configs.ConfigsService method), 4
 create() (cdrouter.devices.DevicesService method), 5
 create() (cdrouter.packages.PackagesService method), 6
 create() (cdrouter.users.UsersService method), 13
 create_or_edit() (cdrouter.annotations.AnnotationsService method), 9
 create_or_edit() (cdrouter.highlights.HighlightsService method), 9

D

decode() (cdrouter.captures.CapturesService method), 9
 delete() (cdrouter.annotations.AnnotationsService method), 9
 delete() (cdrouter.CDRouter method), 3
 delete() (cdrouter.configs.ConfigsService method), 4
 delete() (cdrouter.devices.DevicesService method), 5
 delete() (cdrouter.highlights.HighlightsService method), 9
 delete() (cdrouter.imports.ImportsService method), 10
 delete() (cdrouter.jobs.JobsService method), 6

delete() (cdrouter.packages.PackagesService method), 6
 delete() (cdrouter.results.ResultsService method), 7
 delete() (cdrouter.tags.TagsService method), 11
 delete() (cdrouter.users.UsersService method), 13
 delete_id() (cdrouter.CDRouter method), 3
 delete_testvar() (cdrouter.configs.ConfigsService method), 4
 DevicesService (class in cdrouter.devices), 5
 diagnostics() (cdrouter.system.SystemService method), 11
 download() (cdrouter.captures.CapturesService method), 9
 download_logdir_archive() (cdrouter.results.ResultsService method), 7

E

edit() (cdrouter.CDRouter method), 3
 edit() (cdrouter.configs.ConfigsService method), 4
 edit() (cdrouter.devices.DevicesService method), 5
 edit() (cdrouter.jobs.JobsService method), 6
 edit() (cdrouter.packages.PackagesService method), 6
 edit() (cdrouter.results.ResultsService method), 7
 edit() (cdrouter.tags.TagsService method), 11
 edit() (cdrouter.testresults.TestResultsService method), 8
 edit() (cdrouter.users.UsersService method), 13
 edit_preferences() (cdrouter.system.SystemService method), 11
 edit_shares() (cdrouter.CDRouter method), 3
 edit_shares() (cdrouter.configs.ConfigsService method), 4
 edit_shares() (cdrouter.devices.DevicesService method), 5
 edit_shares() (cdrouter.packages.PackagesService method), 6
 edit_shares() (cdrouter.results.ResultsService method), 7
 edit_testvar() (cdrouter.configs.ConfigsService method), 4
 export() (cdrouter.CDRouter method), 3
 export() (cdrouter.configs.ConfigsService method), 4
 export() (cdrouter.devices.DevicesService method), 5
 export() (cdrouter.packages.PackagesService method), 7
 export() (cdrouter.results.ResultsService method), 7
 ExportsService (class in cdrouter.exports), 10

G

get() (cdrouter.annotations.AnnotationsService method), 9
 get() (cdrouter.captures.CapturesService method), 9
 get() (cdrouter.CDRouter method), 3
 get() (cdrouter.configs.ConfigsService method), 4
 get() (cdrouter.devices.DevicesService method), 5
 get() (cdrouter.highlights.HighlightsService method), 9
 get() (cdrouter.imports.ImportsService method), 10
 get() (cdrouter.jobs.JobsService method), 6

get() (cdrouter.packages.PackagesService method), 7
 get() (cdrouter.results.ResultsService method), 7
 get() (cdrouter.tags.TagsService method), 11
 get() (cdrouter.testresults.TestResultsService method), 8
 get() (cdrouter.users.UsersService method), 13
 get_commit_request() (cdrouter.imports.ImportsService method), 10
 get_error() (cdrouter.testsuites.TestsuitesService method), 12
 get_group() (cdrouter.testsuites.TestsuitesService method), 12
 get_id() (cdrouter.CDRouter method), 3
 get_label() (cdrouter.testsuites.TestsuitesService method), 12
 get_log() (cdrouter.testresults.TestResultsService method), 8
 get_log_plaintext() (cdrouter.testresults.TestResultsService method), 8
 get_logdir_file() (cdrouter.results.ResultsService method), 7
 get_module() (cdrouter.testsuites.TestsuitesService method), 12
 get_networks() (cdrouter.configs.ConfigsService method), 4
 get_new() (cdrouter.configs.ConfigsService method), 5
 get_plaintext() (cdrouter.configs.ConfigsService method), 5
 get_preferences() (cdrouter.system.SystemService method), 11
 get_shares() (cdrouter.CDRouter method), 4
 get_shares() (cdrouter.configs.ConfigsService method), 5
 get_shares() (cdrouter.devices.DevicesService method), 5
 get_shares() (cdrouter.packages.PackagesService method), 7
 get_shares() (cdrouter.results.ResultsService method), 7
 get_test() (cdrouter.testsuites.TestsuitesService method), 12
 get_test_metric() (cdrouter.results.ResultsService method), 7
 get_test_metric_csv() (cdrouter.results.ResultsService method), 7
 get_testvar() (cdrouter.configs.ConfigsService method), 5
 get_testvar() (cdrouter.testsuites.TestsuitesService method), 12

H

HighlightsService (class in cdrouter.highlights), 9
 HistoryService (class in cdrouter.history), 10
 hostname() (cdrouter.system.SystemService method), 11

I

ImportsService (class in cdrouter.imports), 10
 info() (cdrouter.system.SystemService method), 11
 info() (cdrouter.testsuites.TestsuitesService method), 12

interfaces() (cdrouter.system.SystemService method), 11

J

JobsService (class in cdrouter.jobs), 6

L

latest_lounge_release() (cdrouter.system.SystemService method), 11

launch() (cdrouter.jobs.JobsService method), 6

list() (cdrouter.annotations.AnnotationsService method), 9

list() (cdrouter.captures.CapturesService method), 9

list() (cdrouter.CDRouter method), 4

list() (cdrouter.configs.ConfigsService method), 5

list() (cdrouter.devices.DevicesService method), 5

list() (cdrouter.highlights.HighlightsService method), 9

list() (cdrouter.history.HistoryService method), 10

list() (cdrouter.imports.ImportsService method), 10

list() (cdrouter.jobs.JobsService method), 6

list() (cdrouter.packages.PackagesService method), 7

list() (cdrouter.results.ResultsService method), 8

list() (cdrouter.tags.TagsService method), 11

list() (cdrouter.testresults.TestResultsService method), 8

list() (cdrouter.users.UsersService method), 13

list_csv() (cdrouter.results.ResultsService method), 8

list_csv() (cdrouter.testresults.TestResultsService method), 8

list_errors() (cdrouter.testsuites.TestsuitesService method), 12

list_groups() (cdrouter.testsuites.TestsuitesService method), 12

list_labels() (cdrouter.testsuites.TestsuitesService method), 12

list_logdir() (cdrouter.results.ResultsService method), 8

list_modules() (cdrouter.testsuites.TestsuitesService method), 12

list_tests() (cdrouter.testsuites.TestsuitesService method), 12

list_testvars() (cdrouter.configs.ConfigsService method), 5

list_testvars() (cdrouter.testsuites.TestsuitesService method), 12

live() (cdrouter.system.SystemService method), 11

lounge_update_license() (cdrouter.system.SystemService method), 11

lounge_upgrade() (cdrouter.system.SystemService method), 11

M

manual_update_license() (cdrouter.system.SystemService method), 11

manual_upgrade() (cdrouter.system.SystemService method), 11

P

PackagesService (class in cdrouter.packages), 6

patch() (cdrouter.CDRouter method), 4

pause() (cdrouter.results.ResultsService method), 8

pause_end_of_loop() (cdrouter.results.ResultsService method), 8

pause_end_of_test() (cdrouter.results.ResultsService method), 8

post() (cdrouter.CDRouter method), 4

R

restart() (cdrouter.system.SystemService method), 11

ResultsService (class in cdrouter.results), 7

S

search() (cdrouter.testsuites.TestsuitesService method), 12

send_to_cloudshark() (cdrouter.captures.CapturesService method), 9

set_stats() (cdrouter.results.ResultsService method), 8

single_stats() (cdrouter.results.ResultsService method), 8

stage_import_from_file() (cdrouter.imports.ImportsService method), 10

stage_import_from_filesystem() (cdrouter.imports.ImportsService method), 10

stage_import_from_url() (cdrouter.imports.ImportsService method), 10

stop() (cdrouter.results.ResultsService method), 8

stop_end_of_loop() (cdrouter.results.ResultsService method), 8

stop_end_of_test() (cdrouter.results.ResultsService method), 8

summary() (cdrouter.captures.CapturesService method), 9

SystemService (class in cdrouter.system), 10

T

TagsService (class in cdrouter.tags), 11

TestResultsService (class in cdrouter.testresults), 8

TestsuitesService (class in cdrouter.testsuites), 12

time() (cdrouter.system.SystemService method), 11

U

unpause() (cdrouter.results.ResultsService method), 8

upgrade_config() (cdrouter.configs.ConfigsService method), 5

UsersService (class in cdrouter.users), 12